

Two Boiler Lead - Lag Piping

Boiler Model Numbers	Recommended Primary Piping Size - 20 Degree Delta T	Recommended Primary Circulator - 20 Degree Delta T	Recommended Primary Piping Size - 30 Degree Delta T	Recommended Primary Circulators - 30 Degree Delta T	Recommended Secondary Piping Size - 20 Degree Delta T
Two DK2-3	1" or 1 1/4"	Taco 007IFC*	1"	Taco 005IFC*	1 1/2" Cop. or Blk.
Two DK2-4	1 1/4"	Taco 007F**	1"	Taco 007IFC*	2" Cop. or 1 1/2" Blk.
Two DK2-5	1 1/4"	Taco 0010F**	1 1/4"	Taco 007F**	2" Cop. or Blk.
Two DK2-6	1 1/2"	Taco 0012F**	1 1/4"	Taco 0012F**	2" Cop. or Blk.
Two DK2-7	1 1/2"	Taco 0011F**	1 1/4"	Taco 0012F**	2" Cop. or Blk.
Two DK2-8	1 1/2"	Taco 0013F**	1 1/2"	Taco 0014F**	2" Cop. or Blk.

* Or Equivalent

** Or Equivalent, With External Flow Check Installed On Primary Loop