



PENSOTTI
NORTH AMERICA

AMERICA'S BEST HEATING VALUE

Appliance Model	Burner Model	Air Tube Combination	Insertion Length	Nozzle	Pump Pressure	In-put GPH	Turbulator	Air Setting
BL-3 (S1-18)	F3	SBT	3 1/4"	.50 X 60° W	180	0.70	0.5	3.0
BL-4 (S1-26)	F5	SBT	3 1/4"	.75 X 60° W	185	1.00	0.5	3.0
BL-5 (S1-34)	F5	SBT	3 1/4"	1.00 X 60° W	160	1.25	2.5	3.3
BL-6 (S1-42)	F5	SBT	3 1/4"	1.20 X 60° W	160	1.55	3.5	5.5
BL-7 (S1-50)	F10	SBT	3 1/4"	1.50 X 60° W	150	1.80	1.0	4.1
S2-58	F10	SBT	2 1/2"	1.65 X 60° B	175	2.20	2.5	4.0
S2-69	F10	SBT	2 1/2"	1.75 X 60° B	165	2.60	3.5	4.9
S2-80	F10	SBT	2 1/2"	2.25 X 60° B	150	3.00	4.5	5.7
S3-100	F15	SBT	2 1/2"	2.50 X 60° B	150	3.30	1.0	3.4
S3-116	F15	SBT	2 1/2"	3.00 X 60° B	150	3.80	1.5	3.6
S3-132	F15	SBT	2 1/2"	3.50 X 60° B	150	4.30	2.0	4.2
S3-148	F15	SBT	2 1/2"	3.50 X 60° B	175	4.90	3.0	4.9
S3-180	F20	SBT	2 1/2"	4.00 X 60° B	175	5.40	3.0	Lo3.2,Hi5.5
S3-180	F20	SBT	2 1/2"	4.50 X 60° B	170	5.90	4.0	Lo3.4,Hi6.0
SIDEWALL VENTED APPLICATIONS								
BL-3	BF-3	LBT	3 1/4"	.60 X 60° W	145	0.70	1.0	5.0
BL-4	BF-5	LBT	3 1/4"	.85 X 60° W	145	1.00	2.0	4.0
BL-5	BF-5	LBT	3 1/4"	1.00 X 60° W	145	1.25	3.0	5.0
DK2-3	F3	VSBT	3"	.55 X 70° B	160	0.70	0.0	3.6
DK2-4	F5	VSBT	3"	.85 X 60° B	140	1.00	2.0	2.8
DK2-5	F5	VSBT	3"	1.00 X 60° W	156	1.25	3.0	3.0
DK2-6	F5	VSBT	3"	1.10 X 60° W	160	1.39	2.0	4.8
DK2-7	F10	VSBT	3"	1.35 X 45° B	145	1.60	1.0	3.0
DK2-8	F10	VSBT	3"	1.50 X 45° B	145	1.80	2.0	3.0
SIDEWALL VENTED APPLICATIONS								
DK2-3	BF3	VSBT	3"	.55 X 70° B	160	0.70	2.0	4.6
DK2-4	BF5	VSBT	3"	.85 X 60° B	140	1.00	1.0	4.4
DK2-5	BF5	VSBT	3"	1.00 X 60° W	156	1.25	2.0	5.6